

GENERAL FEATURES


- Environmentally friendly
- Can be used at vertical or horizontal orientation
- High Reliability and Good Quality
- High gas recombination efficiency
- High Power Density
- Maintenance-Free Operation

APPLICATIONS

- UPS & EPS
- Emergency lighting Systems
- Medical Equipment
- Cable TV Systems
- Alarm Systems
- Electric Test Equipment
- Security Systems

DIMENSIONS & WEIGHT

Length(mm)	134±1
Width(mm)	67±1
Height (mm)	61±1
Total Height(mm)	67±1
Weight(kg)	1.22±3%


COMPLIED STANDARDS

IEC 60896-21/22	JIS C8704
YD/T799	BS6290 part4
GB/T 19639	UL 1989

TECHNICAL SPECIFICATIONS


Nominal Voltage		12V(6 cells per unit)
Design Floating Life @25°C		5 Years
Nominal Capacity @25°C(20 hour rate@0.165A,10.50V)		3.30Ah
Capacity @25°C	10 hour rate (0.31A,10.8V)	3.10Ah
	5 hour rate (0.55A,10.5V)	2.75Ah
	1 hour rate (2.27A,9.6V)	2.27Ah
Internal Resistance	Full Charged Battery@25°C	≤50.0mΩ
Ambient Temperature	Discharge	-20°C ~50°C
	Charge	-20°C ~50°C
	Storage	-20°C ~50°C
Max.Discharge Current@25°C		49.5A(5s)
Capacity affected by Temperature (10 hr Capacity)	40°C	102%
	25°C	100%
	0°C	85%
	-15°C	65%
Self - Discharge @25°C		3%
Charge (Constant Voltage) @25°C	Standby Use	Initial Charging Current Less than 0.99A Voltage 13.6-13.8V
	Cycle Use	Initial Charging Current Less than 0.99A Voltage 14.4-14.9V







BATTERY DISCHARGE TABLE
Discharge Constant Current per Cell (Amperes at 25°C)

F.V/Time	5min	10min	15min	30min	45min	1h	2h	3h	5h	8h	10h	20h
1.60V	11.34	8.20	6.46	3.78	2.65	2.27	1.33	0.92	0.58	0.41	0.33	0.174
1.67V	11.14	8.11	6.28	3.71	2.60	2.23	1.31	0.90	0.58	0.40	0.33	0.171
1.70V	10.93	7.88	6.14	3.64	2.55	2.19	1.29	0.88	0.56	0.39	0.32	0.168
1.75V	10.73	7.52	5.96	3.58	2.50	2.15	1.26	0.87	0.55	0.39	0.32	0.165
1.80V	10.31	7.43	5.78	3.44	2.41	2.06	1.21	0.83	0.53	0.37	0.31	0.163

Discharge Constant Power per Cell (Watts at 25°C)

F.V/Time	5min	10min	15min	30min	45min	1h	2h	3h	5h	8h	10h	20h
1.60V	21.84	16.18	12.47	7.28	5.10	4.37	2.57	1.76	1.15	0.79	0.65	0.344
1.67V	21.44	15.90	12.10	7.15	5.00	4.29	2.52	1.73	1.13	0.77	0.64	0.335
1.70V	21.04	15.58	11.78	7.01	4.91	4.21	2.48	1.70	1.11	0.76	0.63	0.330
1.75V	20.65	14.67	11.46	6.88	4.82	4.13	2.43	1.66	1.09	0.75	0.62	0.325
1.80V	19.85	14.21	11.14	6.62	4.63	3.97	2.34	1.60	1.05	0.72	0.60	0.321

PERFORMANCE CHARACTERISTICS



BATTERY CONSTRUCTION

Component	Positive plate	Negative plate	Container & Cover	Safety valve	Terminal	Separator	Electrolyte	Pillar seal
Features	Thick high Sn low Ca grid with special paste	Balanced Pb-Ca grid for improved recombination efficiency	ABS (UL94-V0 optional)	Flame Si-Rubbeand aging resistancer	Female Copper Insert (NO.187)	Advanced AGM separator for high pressure cell design	Dilute high purity sulphuric acid	Two layers epoxy resin seal